



## MACHINE FEATURES


- One piece cast mold, large shocking proof damping and less deformation;
- 45 degree slant bed design, easy to get on and off workpieces, convenient to remove chip, assured of processing accuracy and smoothness;
- 12-station servo turret, more knives positions, achieving multi-functional processing such as turning, boring, drilling, tapping, less processing interference;
- Simple operation interface and programming system, easy to operate, and production efficiency highly improved;

## APPLICATION

The machine is suitable for processing batch continuous heavy parts within a diameter of 46/52mm, with high-precision, high-efficiency, and multi-functional requirements, and widely used in motorcycles, optical instruments, medical equipment, oil pipelines, special motors, hydraulic and pneumatic engineering and other industries.

## STANDARD ACCESSORIES

1 pc user manual, 5 pcs turret tool holders, 4 pcs row knife holders, 1 pc foot switches, 1 set hex wrench, 1 pc collect, 1 pc stop nut



### OPTIONAL ACCESSORIES

Chuck, feeder, chip conveyor, manipulator, turret optional

# MACHINE PARAMETERS

	Item	Unit	RKS-46D	RKS-52D
Processing Capacity	Max rotation diameter	mm	Ф420	Ф420
	Max turning diameter	mm	Ф100	Ф100
	Max cutting length	mm	230	230
	X axis travel	mm	280	280
	Z axis travel	mm	300	300
Spindle	Spindle nose		A2-5	A2-6
	Spindle through-hole diameter	mm	Ф56	Ф66
	Max bar diameter	mm	Ф45	Ф52
	Max rotation speed	r/min	6000	4500
	Spindle motor power	kw	7.5	11
	Spindle drive power	kw	7.5	11
	Chuck diameter/size	inch	6"	8"
Feed Axis	X axis positioning accuracy	mm	0.005	0.005
	Z axis positioning accuracy	mm	0.005	0.005
	X axis repeat positioning accuracy	mm	0.002	0.002
	Z axis repeat of positioning accuracy	mm	0.002	0.002
	X/Z axis fast-moving speed	m/min	24/26	24/26
	X/Z axis motor power	kw	1.7	2.4
Turret	Specification		12 Station	12 Station
	Tool changing speed	S	0.2	0.2
	Turret motor power	kw	1.0	1.0
	Turret drive power	kw	1.0	1.0
Cooling Lubricant System	Cooling pump motor power	kw	0.75	0.75
	Tank capacity	L	70L	70L
Others	Dimension (L*W*H)	mm	2230*1950*2150	2230*1950*2150
	Total Power	kva	13	16
	Weight	kg	2800	2900

www.ricksmachinery.com